

What is the purpose of the Resolution Test Mixture supplied in your Qualification Kits - FAQ

The purpose of the Resolution Test Mixture (RTM) is twofold.

- 1. As a sort of "System Suitability" test, if only to make sure you have prepared the mobile phase correctly.
- 2. To be sure that the test column is not completely degraded.

You could use just a caffeine injection for this purpose. However, by using a mixture of several peaks as in the RTM, you can graph the total observed variance, which is comprised of **column variance + extra column variance**. The intercept of that regression is the extra column variance.

This information can be useful; for example, most of our Agilent 1100/1200 instruments produce a 120uL^2 of extra column volume variance (or 11uL as the standard deviation). This is adequate for most standard size analytical columns, but too large for a short 2.1 mm type column, and that can be a significant finding. Some older instruments have been found to have 800-900 ul^2 of volume variance which would make using a 2.1 mm column for your analysis, not recommended for use with this instrument.

Click <u>HERE</u> for PQ and HSQ kit ordering information.

Printed from the Chrom Resource Center Copyright 2025, All Rights Apply **MicroSolv Technology Corporation** 9158 Industrial Blvd. NE, Leland, NC 28451 Tel: (732) 380-8900 Fax: (910) 769-9435 Email: customers@mtc-usa.com Website: www.mtc-usa.com