PRODUCT SHEET

MICROSOLV TECHNOLOGY CORPORATION
HPLC Columns and Chromatography Accessories

Catalog Number

47451-W-01K-010

Adapter, for use with low to medium pressure HPLC. Waters female to 10-32 male connection, 0.40 mm / 0.016 bore size. Black PEEK. ARE-Applied Research brand. 10/PK.

Additional Info

This finger tightened adapter makes changing from Waters® to more common connections very convenient. This all-PEEK adapter has a Waters® style female screw threaded port on one side and a standard 10-32 screw threaded male connector with a built-in ferrule with a "universal" pilot length.

Maximum Temperature: 100°C

Maximum Pressure: 8,000 psig.

Click HERE for pack of 5.

Click HERE for natural PEEK color version.

The "flat" section on the knurled adapter allows to use a wrench for an extra 1/8 of clockwise turn for tighter sealing or a slight counterclockwise turn to help remove if a tight fitting is too hard for hand removal. The flat section can also be used to hold the adapter in place with a wrench while the Waters male nut is tightened in the adapter.

MicroSolv Technology Corporation
9158 Industrial Blvd. NE, Leland, NC 28451
tel. (732) 380-8900, fax (910) 769-9435
Email: info@mtc-usa.com
Website: www.mtc-usa.com